	型 4. 医最后,是是这个人的是否使用的。 医多种种种种的 人名英格兰 化氯化甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲	12.0
Wat raid	inf, ction method and apparatu	C
Trut I WIL	in outputtieurou attu apparatu	J
The state of the s		1. C. 10

Patent Number:

EP0155479

Publication date:

1985-09-25

Inventor(s):

ROSSLER PETER; FABIAN PETER; GUNDLING MANFRED

Applicant(s)::

HERAEUS ELEKTRODEN (DE)

Requested Patent:

■ EP0155479, A3

Application Number: EP19850101110 19850202

Priority Number(s): DE19843410489 19840322

IPC Classification: EC Classification:

C02F1/76

C02F1/467B2

Equivalents:

AU4018585, CA1263095, DE3410489, DK128385, ES8606207, ZA8502090

Abstract

Known methods for the disinfection or sterilisation of water entail a hypochlorite solution being prepared electrochemically in an electrolysis cell and being metered into the water to be disinfected. In order to make possible low-cost preparation of the hypochlorite solution without great effort under defined conditions in such methods, and to provide a method and an apparatus which are particularly suitable for preparing small amounts of a hypochlorite solution and for discontinuous operation, in one method the water which is to be mixed with a stored brine is directly removed from a pipeline under constant pressure, and the hypochlorite solution which has been generated electrochemically is directly metered into the water to be disinfected. In a corresponding apparatus, the interint of the electrolysis cell is connected to a pipeline under constant pressure, which is connected to a pipeline under constant pressure, which is connected to a pipeline under constant pressure, which is connected to a pipeline under constant pressure, which is connected to a pipeline under constant pressure, which is connected to a pipeline under constant pressure. corresponding apparatus, the inlet into the electrolysis cell is connected to a pipeline under constant pressure, which is opened or closed by a blocking element which is operated by an additional electrical control, and the hypochlorite solution generated in the electrolysis cell is furthermore passed to a metering point in the pipeline, through which the medium to be disinfected flows, via a

direct metering line from the electrolysis cell.

Data supplied from the esp@cenet database - 12